Malibu Electric Medical Spa Treatment Table Specifications Sheet





Toll Free: 1.800.418.0830

www.skinact.com www.spaandequipment.com

International: 818.834.6640

NOTICE

No part of this document may be photocopied, reproduced, or translated into any other language without prior written consent of Spa and Equipment/SkinAct.

The information in this document is subject to change without notice at any time and should not be construed as a commitment by Spa and Equipment/SkinAct.

Spa and Equipment/SkinAct assumes no responsibility for any errors that may be in this document, nor does it make expressed or implied warranty with regard to this material, including, but not limited to, the implied warranties of merchantability and fitness for a particular purpose.

Spa and Equipment/SkinAct shall not be liable for incidental or consequential damages arising out of the furnishing, performance, or use of this document and the program material which it describes.













Toll Free: 1.800.418.0830

www.skinact.com www.spaandequipment.com

International: 818.834.6640

Motor Controls on the Malibu








\KIN\CT
Spa\text{Equipment}

Measurements

83" with head rest and foot rest extended





Measurements



Highlights

Features:

- Three sections
- Fully electric except for rotation
- Head cushion; tilt adjustable/removable
- Leg cushion; adjustable/removable
- Removable arms
- Seat tilt function
- Manual rotation system
- Breather hole

Specifications:

- Dimensions: (L x W x H) 73" x 33" x 25"-37"
- Capacity of 350 lbs
- Headrest extension: +/- 3"
- Backrest angle: 0° to 80°
- Seat angle: 0° to 10°
- Rotation: 0° to 240°
- Footrest angle: 0° to 85°
- Width of the bed without armrest 23" with armrest 33"
- Height up and down: 25" 37"
- Footrest extension: +/- 5.5"
- Colors available: black or white

Warranty Information:

1-year warranty

- * All height measurements are from the ground to the top of the cushion*
- ** All measurements have a 0.25 to 0.75 inch tolerance**
- *** Hand remote control sold separately***

100-120 V 50-60 Hz 200 W

